

EDGE CF Card

Model: EDGE-110M



Product Specifications

Rev : 1.0

Model Number	EDGE-110M
Descriptions	EDGE CompactFlash Card
Hardware Type	CompactFlash Card Type II
Triple band operation	Quad- band 850/900/1800/1900
Wireless bearers	EDGE multislot class 12 and mobile station class B up to 236.8Kbps GPRS multislot class 12 up to 85.6Kbps Voice, SMS, text/data messaging, Fax (Optional)
TECHNICAL DETAILS	RF power (max.) <ul style="list-style-type: none"> • 2W (900 MHz) / 1W (1800 MHz) • 2W (850 MHz) / 1W (1900 MHz) Power consumption (estimates) <ul style="list-style-type: none"> • Standby 12-29 mA • GPRS 310-690 mA • Peak 2 A No extra battery needed.
Interface	Standard Type II Compact Flash PCMCIA 3.3V SIM card interface (3V/1.8V) Analog audio Antenna connector Type: MCX. Antenna can be replaced by external high gain antenna.
Bundle Software Mobile Phone Tool Capability	Send/Receive, broadcasting SMS, MMS. Voice dialing and answering FAX sending and receiving (optional) Auto-installs Internet profile by detecting SIM card Send/Receive e-mail from software, or Outlook. SIM card phone book management can be synchronous to Outlook contacts for easy maintain
System compatibility	Windows Mobile 5.0, Pocket PC 2003 Premium, 2002, 2000, WinCE, WinCE.NET Hardware has been test: <ul style="list-style-type: none"> • iPAQ hx2790/2490/2190, iPAQ 2200,3800 With CF to PCMCIA converter, it can be used for Windows XP, 2000. User also can use Pocket PC or WinCE.Net internal network configuration for browsing Internet without application software.
Accessory	Hands free Earphone. Application software CD. CF to PCMCIA converter (optional) Carrying case (optional)
General information	Dimensions: Gift Box: 16.6x26x5.5 cm Weight: 40g