

GPRS/GSM CF Card

Model : GPRS 11A-CF

Product Specifications

Rev : 1.0

Model Number	GPRS 11A-CF
Descriptions	GPRS CompactFlash Card
Hardware Type	CompactFlash Card Type I
Triple band operation	EGSM 900, DCS 1800 and PCS 1900 Discontinuous receiving for power saving (DRX) Discontinuous transmission (DTX)
Voice	Half rate/Full rate/Enhanced full rate Echo cancellation for hands-free operation
Short message service (SMS)	Mobile terminated/originated, point to point Cell broadcasting (CB) Text and PDU mode
FAX	Group 3, Class 2.0 Alternative speech & facsimile Transparent mode
Supplementary service (SS)	Line identification (CLIP, CLIR, CoLP) Call forwarding (CFU, CFB, CFNRy, CFNRc) Call completion (CW, HOLD, MPTY, CUG, UUS) Advise of charge (AoCI, AoCC) Call barring (BAOC, BOIC, BOIC-exHC, BAIC, BAIC-cxRoam)
Circuit switched data	Upload/download Asynchronous Transparent/non-transparent mode Up to 9.6/14.4Kbps
GPRS Class B, Multi-slot Class 8	4 receiving slots, 1 transmitting slot, 5 maximum active, Simultaneous network registration of GSM & GPRS CS1—CS4 coding scheme supported SMS over GPRS
Interface	50-pin standard Compact Flash Type I Supply voltage: 3.3V 3/5V SIM supported External headset for audio connection AT command set according to GSM 07.05 07.07 including GPRS-specific or extension commands
General information	Dimensions: 63.8 x 42.8 x 3.3 mm (excluding antenna)/ 9.35 (including antenna) mm Weight: 23g(without headset) Operating temperature: -10 C to +55 C
Compatible operating system	Pocket PC 2000/2002/2003, Windows 98SE/ME/2000/XP
Approval	GCF 3.3.0, R&TTE, PTCRB, FCC